

SG01-MR



Replacement Body:

Quickly complete the replacement

## ▪ Specification

HARDWARE FEATURES	
CONNECTION	EUROBLOCK 2 PINS CONNECTED TO IGNITER
ELECTRICAL CHARACTERISTICS	
EXTERNAL POWER SUPPLY FOR ACTIVATION	6V to 24V AC or DC with a minimum of 500 mA during 50 mS.
OPERATION TEMPERATURE(INDOOR)	-10°C to +40°C
OPERATION HUMIDITY(INDOOR)	10% to 40%
GRADO AMBIENTAL SEGÚN EN 50131-5	II
GENERAL	
INSTALLATION METHOD WALL MOUNTING.	See installation manual
DIMENSION (W x H x D)	131 x 119 x 139 mm
SHELL MATERIAL	Plastic
COLOR	WHITE
WEIGHT	600g
DEVICE MANAGEMENT	
ACTIVATION	EXTERNAL DIRECT SUPPLY
PERFORMANCE	
APPROXIMATE ACTIVATION TIME	26s
SMOKE VOLUME PER SHOT	80 m <sup>3</sup>
NUMBER OF SHOTS PER UNIT	1
TIME SINCE ACTIVATION FOR SMOKE GENERATION	0.3 s

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

