

Cross Section	Performance																																																												
	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr style="background-color: #008080; color: white;"> <th colspan="4">Electrical Characteristics:</th> </tr> <tr style="background-color: #008080; color: white;"> <th>Frequency (MHz)</th> <th>Return loss (Min dB)</th> <th>Attenuation Max (dB/100m)</th> <th>NEXT (Min dB)</th> </tr> </thead> <tbody> <tr><td>0.772</td><td>19.4</td><td>1.8</td><td>67.0</td></tr> <tr><td>1</td><td>20.0</td><td>2.0</td><td>65.3</td></tr> <tr><td>4</td><td>23.0</td><td>4.1</td><td>56.3</td></tr> <tr><td>8</td><td>24.5</td><td>5.8</td><td>51.8</td></tr> <tr><td>10</td><td>25.0</td><td>6.5</td><td>50.3</td></tr> <tr><td>16</td><td>25.0</td><td>8.2</td><td>47.3</td></tr> <tr><td>20</td><td>25.0</td><td>9.3</td><td>45.8</td></tr> <tr><td>25</td><td>24.3</td><td>10.4</td><td>44.3</td></tr> <tr><td>31.25</td><td>23.6</td><td>11.7</td><td>42.9</td></tr> <tr><td>62.5</td><td>21.5</td><td>17.0</td><td>38.4</td></tr> <tr><td>100</td><td>20.1</td><td>22.0</td><td>35.3</td></tr> </tbody> </table>	Electrical Characteristics:				Frequency (MHz)	Return loss (Min dB)	Attenuation Max (dB/100m)	NEXT (Min dB)	0.772	19.4	1.8	67.0	1	20.0	2.0	65.3	4	23.0	4.1	56.3	8	24.5	5.8	51.8	10	25.0	6.5	50.3	16	25.0	8.2	47.3	20	25.0	9.3	45.8	25	24.3	10.4	44.3	31.25	23.6	11.7	42.9	62.5	21.5	17.0	38.4	100	20.1	22.0	35.3								
Electrical Characteristics:																																																													
Frequency (MHz)	Return loss (Min dB)	Attenuation Max (dB/100m)	NEXT (Min dB)																																																										
0.772	19.4	1.8	67.0																																																										
1	20.0	2.0	65.3																																																										
4	23.0	4.1	56.3																																																										
8	24.5	5.8	51.8																																																										
10	25.0	6.5	50.3																																																										
16	25.0	8.2	47.3																																																										
20	25.0	9.3	45.8																																																										
25	24.3	10.4	44.3																																																										
31.25	23.6	11.7	42.9																																																										
62.5	21.5	17.0	38.4																																																										
100	20.1	22.0	35.3																																																										
Marking																																																													
Description																																																													
Rated Temperature (°C) 75 Product Standard Certification	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr style="background-color: #008080; color: white;"> <th>Frequency (MHz)</th> <th>PSNEXT (Min dB)</th> <th>ELFEXT (Min dB/100m)</th> <th>PSELFEXT (Min dB/100m)</th> <th>Delay (ns/100m)</th> </tr> </thead> <tbody> <tr><td>0.772</td><td>64.0</td><td>66.0</td><td>63.0</td><td>575.0</td></tr> <tr><td>1</td><td>62.3</td><td>63.8</td><td>60.8</td><td>570.0</td></tr> <tr><td>4</td><td>53.3</td><td>51.7</td><td>48.7</td><td>552.0</td></tr> <tr><td>8</td><td>48.8</td><td>45.7</td><td>42.7</td><td>546.7</td></tr> <tr><td>10</td><td>47.3</td><td>43.8</td><td>40.8</td><td>545.4</td></tr> <tr><td>16</td><td>44.3</td><td>39.7</td><td>36.7</td><td>543.0</td></tr> <tr><td>20</td><td>42.8</td><td>37.7</td><td>34.7</td><td>542.0</td></tr> <tr><td>25</td><td>41.3</td><td>35.8</td><td>32.8</td><td>541.2</td></tr> <tr><td>31.25</td><td>39.9</td><td>33.9</td><td>30.9</td><td>540.4</td></tr> <tr><td>62.5</td><td>35.4</td><td>27.8</td><td>24.8</td><td>538.6</td></tr> <tr><td>100</td><td>32.3</td><td>23.8</td><td>20.8</td><td>537.6</td></tr> </tbody> </table>	Frequency (MHz)	PSNEXT (Min dB)	ELFEXT (Min dB/100m)	PSELFEXT (Min dB/100m)	Delay (ns/100m)	0.772	64.0	66.0	63.0	575.0	1	62.3	63.8	60.8	570.0	4	53.3	51.7	48.7	552.0	8	48.8	45.7	42.7	546.7	10	47.3	43.8	40.8	545.4	16	44.3	39.7	36.7	543.0	20	42.8	37.7	34.7	542.0	25	41.3	35.8	32.8	541.2	31.25	39.9	33.9	30.9	540.4	62.5	35.4	27.8	24.8	538.6	100	32.3	23.8	20.8	537.6
Frequency (MHz)	PSNEXT (Min dB)	ELFEXT (Min dB/100m)	PSELFEXT (Min dB/100m)	Delay (ns/100m)																																																									
0.772	64.0	66.0	63.0	575.0																																																									
1	62.3	63.8	60.8	570.0																																																									
4	53.3	51.7	48.7	552.0																																																									
8	48.8	45.7	42.7	546.7																																																									
10	47.3	43.8	40.8	545.4																																																									
16	44.3	39.7	36.7	543.0																																																									
20	42.8	37.7	34.7	542.0																																																									
25	41.3	35.8	32.8	541.2																																																									
31.25	39.9	33.9	30.9	540.4																																																									
62.5	35.4	27.8	24.8	538.6																																																									
100	32.3	23.8	20.8	537.6																																																									
Application Horizontal Wiring in LAN																																																													
Reference Standard UL Subject 444,EIA/TIA568 & ISO/IEC 11801																																																													
Construction																																																													
Conductor Solid Bare Copper AWG 24 Conductor Dia. (mm) 0.46 Insulation PE Average Thickness(mm) 0.190 Min. Point Thickness(mm) 0.185 Insulation Dia.(±0.01mm) 0.84 Twisted Pair Dia.(±0.02mm) 1.68 Assembly Dia.(±0.2mm) 3.6	1.0-100.0MHz Impedance (ohms) 100 ± 15 1.0-100.0MHz Delay Skew (ns/100m) <=45 Pair-to-Ground Capacitance Unbalance (pF/100m) <=330 Max. Conductor DC Resistance 20°C (ohms/km) 93.8 Resistance Unbalance (%) <=5																																																												
Jacket PVC Average Thickness(mm) 0.55 Min. Point Thickness(mm) 0.5 Outer Dia.(±0.2mm) 4.70																																																													
Rip Cord Per request																																																													
Color																																																													
Insulation colors are: Blue,White/Blue Orange,White/Orange Green,White/Green Brown,White/Brown Jacket colors: Per request	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr style="background-color: #008080; color: white;"> <th colspan="4">Mechanical Characteristics:</th> </tr> <tr style="background-color: #008080; color: white;"> <th>Test Object</th> <th>Test Material</th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>Before</td> <td>Tensile Strength (Mpa)</td> <td></td> <td>>=13.8</td> </tr> <tr> <td>Aging</td> <td>Elongation (%)</td> <td></td> <td>>=100</td> </tr> <tr> <td>After</td> <td>Tensile Strength (Mpa)</td> <td></td> <td>>=85% of unaged</td> </tr> <tr> <td>Aging</td> <td>Elongation (%)</td> <td></td> <td>>=50% of unaged</td> </tr> <tr> <td>Cold Bend(-20±2°Cx4hrs)</td> <td></td> <td></td> <td>No crack</td> </tr> </tbody> </table>	Mechanical Characteristics:				Test Object	Test Material			Before	Tensile Strength (Mpa)		>=13.8	Aging	Elongation (%)		>=100	After	Tensile Strength (Mpa)		>=85% of unaged	Aging	Elongation (%)		>=50% of unaged	Cold Bend(-20±2°Cx4hrs)			No crack																																
Mechanical Characteristics:																																																													
Test Object	Test Material																																																												
Before	Tensile Strength (Mpa)		>=13.8																																																										
Aging	Elongation (%)		>=100																																																										
After	Tensile Strength (Mpa)		>=85% of unaged																																																										
Aging	Elongation (%)		>=50% of unaged																																																										
Cold Bend(-20±2°Cx4hrs)			No crack																																																										
Marking																																																													