

NC-PX3

Conventional Fire and Extinguishing Panel - 3 Zone

Overview

The New Conventional fire control panels offer state of the art architecture in configurations that deliver an uncomplicated solution for small to mid-sized conventional applications. With their clean and attractive contemporary design, they fits with any decor. The basic and intuitive user interface with icons make easy their application everywhere.

With support for multiple lines of conventional detectors and accessories, these quick-to-configure systems offer versatility that benefits building owners and installation/maintenance companies alike.

The Panel

The NC-PX3 is a conventional fire alarm and extinguishing control panel. It is supplied in local language with 3 fire zones that support up to 32 devices per zone. These zones may be configured for extinguishing in single zone or double zone configuration in any combination of zones. In addition the panel offers supervised outputs for first stage notification, second stage notification as well as optical warning indicators and actuator activation. Standard relay outputs are provided for EN54 compliance and system status notification, as well as multiple inputs for system control.

Options

The panels support 2 types of auxiliary relay boards, one with 4 standard relays, and one with 4 supervised relays. With these boards the panel outputs may be expanded with up to 16 additional outputs.

Approvals & Compliance

The product line carries the following accreditations:

- EN54:2, EN54:4 and CE approved
- CPD certified
- EN12094-1 certified

- WEEE compliant
- RoHS compliant

Detalles

- Modern, elegant design with basic and intuitive user interface with icons.
- Easy removable parts for quick and easy installation
- Normal & head-out supervision support per zone
- Three detection zones
- Single zone, double zone or any combination of zones configurable for release
- 6 Pre-configured relays and 8 supervised inputs for extinguishing control
- Configurable fire routing, sounder, extinguishing, reset and door monitoring delays
- Configurable "Hold Mode" type-A or type-B
- Sounders configurable for pulsing or continuous operation
- Extinguishing agent flow confirmation
- Continuous or resettable 24 VDC auxiliary supply
- Auxiliary standard & supervised relay output support
- Default support for special functions such as: - EN54 compliant user access levels - Basic & Advanced level configuration - mixed zones - front panel diagnostics with test & disable control - one-man walk test

NC-PX3

Conventional Fire and Extinguishing Panel - 3 Zone

Especificaciones técnicas

General

Capacidad máxima del sistema (número de dispositivos) hasta 96

Eléctrico

Tipo de fuente de alimentación VAC
Consumo de corriente 4 A @ 24 VDC
Voltaje de funcionamiento 110 VAC @ 50 Hz or 230 VAC @ 50 Hz (+10% -15%)
Cable type: 3 x 1.5 mm² (live, neutral, earth)
Consumo de corriente 3.15 A @ 110/1.5 A @ 240 VAC
2.78 A (Alarm, no devices)
0.39 A (Quiescent, no devices)

Lazo

Capacidad máxima del lazo 3

Zona

Máxima capacidad de zona hasta 3
Voltaje de funcionamiento 22 VDC (18 to 24 VDC)
Cantidad de dispositivos por lazo 20 max.
Calificación 65 mA (max. Load)
Ratio del cable 40 ohm (max. rsistance), 500 nF (max. capacitance)

Batería en reposo

Capacidad 2 x 12 V, 12 Ah (SLA)

Físico

Factor de forma Medio
Dimensiones físicas 440 x 480 x 140 mm (W x H x D)
Peso neto 3.9 kg (without battery)
Peso de envío 6 kg
Color Gris (RAL 7035)
Tipo de Montaje Montaje en Superficie
Entradas de cable Ø 20 mm - 20 / 2 / 26 (top / bottom / rear)

Medioambiental

Temperatura de funcionamiento -5 to +50°C
Temperatura de almacenamiento -20 to +70°C
Humedad relativa 10 to 95% noncondensing
Entorno Interior
Clasificación IP IP30

Regulador

Cumplimiento CPD, RoHS, WEEE
Certificación EN12094-1, EN54-2, EN54-4

Supervised Inputs

6
Use MCP Start, MCP Hold, MCP Abort, Pressure Switch, Gas Flow, Door Monitor

Non Supervised Inputs

2
Use Auto/Manual mode, Remote Reset

Supervised Outputs

4
Use Fire Sounders, Extinguishing Sounders, Optical Indications, Actuator
Notification 2 x 500 mA @ 24 VDC
Visual indicators 1 x 500 mA @ 24 VDC
Actuator 1 x 1 A @ 24 VDC

Non Supervised Outputs

4
Use Hold Mode, Abort Mode, Manual Mode, Release Indication
Specification 6 x 2 A @ 30 V

Auxilliary Supply Output

Output voltage 24 VDC (21 to 28 VDC)
Load (max) 250 mA